

LIST OF FIGURES

	Page
Figure 1. Tiered switching centers.	5
Figure 2. Bell system 5-tier heirarchical structure.	5
Figure 3. Tiered hierarchy plus high usage trunks.	7
Figure 4. Dynamic nonhierarchical routing.	7
Figure 5. The DNHR switching and signalling hierarchy.	8
Figure 6. The cellular mobile telephone service network.	10
Figure 7. Typical mobile cellular radio telephone base station.	15
Figure A1. Reinforced concrete wall and FDTD computational volume.	23
Figure A2. Transmission coefficients for a concrete wall with a 2 dimensional re-bar lattice: $P = 15.24$ cm, $D = 1.91$ cm, and $W = 20.32$ cm.	25
Figure A3. Transmission coefficients for a concrete wall with a 2 dimensional re-bar lattice: $P = 7.62$ cm, $D = 1.91$ cm, and $W = 20.32$ cm.	26
Figure A4. Transmission coefficients for a concrete wall with a 2 dimensional re-bar lattice: $P = 15.24$ cm, $D = 5.08$ cm, and $W = 20.32$ cm.	26
Figure B1. Magnitude of the normalized transfer impedance $Z_t(s)/R_{dc}$ versus gd for a tubular cable.	28
Figure B2. A braided shield (a) and its surface (b).	29